ADA POOL LIFTS

| Maintenance Task to Perform | Daily | Weekly | Monthly |
|---|-------|--------|---------|
| Charge battery overnight* | | | |
| Rinse lift with non-chlorinated water and wipe dry with soft, non-abrasive cloth** | | | |
| Clean with Spectra-Clean™ to passivate the stainless steel | | | |
| Clean and Apply Dielectric Grease to Control Box and Battery | | | |
| Test lift for full operation*** | | | |
| Visual Inspection—check for visible damage and corrosion, and to ensure that all hardware is snug | | | |
| Lubricate all pivot points with Light 3-in-1 Oil (WD-40) | | | |
| Grease Lower Bearing Assembly with FDA-approved Grease using a grease gun through oil zerk | | | |

IMPORTANT NOTES:

*When not in use, remove the battery from the lift and store it on the charger to maintain the battery's charge.

**Use only fresh water to wash your lift, not pool water!

**NOTE: Do not use high pressure power wash to rinse--damage can occur!

***DO NOT manually move the lift left and right by pushing it (unless instructed otherwise by a Spectrum technician.)

Please make copies for regular use in your facility

Need help? Please contact our friendly customer service team: techsupport@spectrumproducts.com

or call us at 800-791-8056



7100 Spectrum Lane | Missoula MT 59808 www.spectrumproducts.com | info@spectrumproducts.com | 800.791.8056